

## PRODUCT SPECIFICATIONS

499LC-xxx, 499SC-xxx, 499ST-xxx, 49886-SH1

# FASTSPLICE™ Fusion Splice-On Connectors

## APPLICATION

Leviton's FASTSPLICE Fusion Splice-On Connectors provide uncompromised optical and environmental performance in field installable LC, SC and ST connector types. They support the rapid construction and maintenance requirements of today's enterprise and data center applications, utilizing readily available fusion splicers. Used in combination with one-ended pre-terminated cable assemblies, the field installable fusion splice-on connectors offer the contractor the ability to install the pre-terminated end, and then cut the blunt end to length, providing flexibility and time savings. FASTSPLICE connectors are also suitable for most central office, MDU cabling, outside plant CATV and FTTx applications.



## SPECIFICATION

FASTSPLICE fusion splice-on fiber optic connectors shall meet or exceed the requirements described in ANSI/TIA-568-3.E and 604 physical standards. All plastic components shall be molded of 94 V-0 rated plastic. The connectors shall be factory-polished and field installable. Connectors shall be available in LC, SC, and ST single-mode and multimode configurations. Maximum insertion loss shall be = 0.25 dB per connector, and return loss shall be  $\geq 65$  dB for single-mode APC connectors,  $\geq 55$  dB for single-mode UPC connectors, and  $\geq 30$  dB for multimode PC connectors.

## FEATURES

- Factory polished and field installable
- Compatible with most common fusion splicers including AFL/Fujikura, Sumitomo, Fitel, and UCL Swift (UCL Swift holder PN F-20/30 required)
- Connectors support 900 micron buffered fiber or 250 micron coated fiber with appropriate fanout kit or furcation tubing
- Connectors sold in packs of 12
- Individual connectors are in reclosable clamshells with part identification and strip template
- LC connectors can be joined using optional duplex clips, Leviton part number 49991-CLP
- The Leviton FASTSPLICE Tool Kit includes tools to access and strip common fiber cable constructions, and also several accessories specific to fusion splicing (see FASTSPLICE Tool Kit 49800-SOC specification for details)
- Each FASTSPLICE Universal Ferrule Holder (sold separately, 49886-SH1) supports up to 100 or more splice-on connector terminations

## STANDARDS & REGULATIONS

- TIA-568.3-E
- RoHS 2 per 2011/65/eu, UL 94 VO Rating
- LC Type: IEC 61754-20, EIA/TIA-604-10, FOCIS-10
- SC Type: IEC 61754-4, EIA/TIA-604-3, FOCIS-3
- ST Type: IEC 61754-2, EIA/TIA-604-2 FOCIS-2

## COUNTRY OF ORIGIN

Mexico

## WARRANTY INFORMATION

For Leviton product warranties, go to [leviton.com/ns/warranty](http://leviton.com/ns/warranty)

499LC-xxx, 499SC-xxx, 499ST-xxx, 49886-SH1

## PRODUCT SPECIFICATIONS

**499LC-xxx, 499SC-xxx, 499ST-xxx, 49886-SH1**

### PHYSICAL SPECIFICATIONS

Parameter	Value
Insertion Loss (Multimode)	Max: 0.25 dB*
Insertion Loss (Single-Mode)	Max: 0.25 dB*
Return Loss (Multimode)	≥ 30 dB (PC)
Return Loss (Single-Mode)	≥ 65 dB (APC), ≥ 55 dB (UPC)
Operating Temperature:	-40 °C to +75 °C
LC and SC Polish:	SM APC and UPC, MM PC
ST Polish:	SM UPC, MM PC

\*Insertion loss value is influenced by handling, cleanliness and quality of splice.

### FASTSPlice™ FUSION SPLICE ON CONNECTORS

Description	Part No.
<b>900 µm 12-Pack</b>	
LC SM APC OS2 Green 900 µm	499LC-GN9
LC SM OS2 Blue 900 µm	499LC-BL9
LC MM OM1 Beige 900 µm	499LC-BG9
LC MM OM3/4 Aqua 900 µm	499LC-AQ9
SC SM APC OS2 Green 900 µm	499SC-GN9
SC SM OS2 Blue 900 µm	499SC-BL9
SC MM OM1 Beige 900 µm	499SC-BG9
SC MM OM3/4 Aqua 900 µm	499SC-AQ9
ST SM OS2 Blue 900 µm	499ST-BL9
ST MM OM1 Beige 900 µm	499ST-BG9
ST MM OM3/4 Aqua 900 µm	499ST-AQ9
Universal LC/ST/SC Ferrule Holder, 10-pack*	49886-SH1
LC Duplex Clip, pack of 6, clear	49991-CLP
FASTSPlice Tool Kit	49800-SOC

\*For a list of compatible splicers, visit [Leviton.com/FASTSPlice](http://Leviton.com/FASTSPlice).

**499LC-xxx, 499SC-xxx, 499ST-xxx, 49886-SH1**

For further support information, visit [leviton.com/ns/support](http://leviton.com/ns/support)

Page 2 of 2

**USA**  
Network Solutions Headquarters  
+1 (800) 722 2082  
[infoUSA@leviton.com](mailto:infoUSA@leviton.com)  
Leviton Berk-Tek Cable: +1 (800) 237 5835  
[berktek.info@leviton.com](mailto:berktek.info@leviton.com)

**Asia Pacific**  
+852 3620 2602  
[infoAPAC@leviton.com](mailto:infoAPAC@leviton.com)

**Canada**  
+1 (800) 461 2002  
[infoCanada@leviton.com](mailto:infoCanada@leviton.com)

**Europe**  
+44 (0) 1592 772124  
[infoEurope@leviton.com](mailto:infoEurope@leviton.com)

**Latin America**  
MX: +52 (55) 2128 6286  
LATAM: +52 (55) 2333 5963  
[infoLATAM@leviton.com](mailto:infoLATAM@leviton.com)

**Middle East & Africa**  
+971 (4) 247 9800  
[infoMEA@leviton.com](mailto:infoMEA@leviton.com)

NETWORK SOLUTIONS PRODUCTS ARE AVAILABLE WORLDWIDE IN OVER 100 COUNTRIES. VISIT US ONLINE AT [LEVITON.COM/NS](http://Leviton.com/ns) TO LEARN MORE.